

Juniper.JN0-663.v2022-05-11.q75

Exam Code:	JN0-663
Exam Name:	Service Provider Routing and Switching, Professional (JNCIP-SP)
Certification Provider:	Juniper
Free Question Number:	75
Version:	v2022-05-11
# of views:	1037
# of Questions views:	750
https://www.dumpsdb.com/dumps/Juniper/JN0-663/Juniper.JN0-663.v2022-05-11.q75	

NEW QUESTION: 1

Exhibit:

Referring to the exhibit, which three statements are correct? (Choose three.)

- A. The ESI is 00:22:22:22:22:22:22:22:22.
- B. The router with the IP address 10.101.100.3 is the originator of this route.
- C. This ESI Auto-Discovery route is used for designated forwarder election.
- D. This route contains the MAC address of an end host.
- E. This route is an EVPN Type-1 route.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 2

Exhibit:

You notice an inconsistency between the routing table and the OSPF database, as shown in the exhibit.

What are two reasons for this behavior? (Choose two.)

- A. An OSPF export policy is being applied to the route.
- B. An OSPF import policy is being applied to the route.
- C. The LSA is a Type 4 LSA.
- D. The LSA is a Type 5 LSA.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 3

Exhibit:

Your network is connected to two different ISPs and you notice that they are using your network for transit traffic.

In this scenario, which two configuration statements will solve this problem? (Choose two.)

- A. set policy-options as-path LOCAL-ROUTES " (65310 | 65441) +"
- B. set policy-options as-path LOCAL-ROUTES "(")"
- C. set policy-options policy-statement ISP term REST then reject
- D. set policy-options policy-statement ISP term ROUTES then reject

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 4

Exhibit:

Referring to the exhibit, you are asked to summarize all routes in the 10.10.0 0/22 address range ensuring that a single summary route is present in area 49.0002 while the IS-IS internal contributing routes are restricted to area 49.0001. All other routes must not be affected.

Which two operations would have to be performed on R2 to accomplish this task? (Choose two.)

- A. Include the from level 1 match criteria when referencing the summary route.
- B. Create and apply a policy with a single term to accept only the summary route.
- C. Include the to level 2 match criteria when referencing the summary route.
- D. Create and apply a policy with two terms; one to accept the summary route and one to reject the contributing routes.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 5

Exhibit:

R2 is receiving the same route from R1 and R3. You must ensure that you can load balance traffic for that route.

Referring to the exhibit, which two configuration changes will allow load balancing? (Choose two.)

- A. Configure multipath under the global BGP configuration.
- B. Apply the prepend policy as an import policy under group R3.
- C. Apply the prepend policy as an import policy under group R1.
- D. Configure multipath under group R1.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 6

You manage an MX Series device which includes the configuration shown in the exhibit. Traffic marked with DSCP 000011 is entering the ge-1/0/4 interface at 102 Mbps. The traffic exits the device on the ge-1/0/5 interface. No other traffic is transiting the router.

In this scenario, what happens to traffic exceeding 100 Mbps?

- A. Traffic exceeding 100 Mbps is redirected to a rate limiter.
- B. Traffic exceeding 100 Mbps is buffered.
- C. Traffic exceeding 100 Mbps is dropped.

D. Traffic exceeding 100 Mbps is forwarded.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 7

Exhibit:

You must configure an OSPF virtual link to facilitate communication between Area 0 and Area 20. Referring to the exhibit, which two addresses should you use as the neighbor IDs of the virtual link endpoints?

(Choose two.)

- A. The address that is associated with R4's router ID.
- B. The address that is associated with R2's xe-1/2/0 interface.
- C. The address that is associated with R2's router ID.
- D. The address that is associated with R4's xe-0/0/1 interface.

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 8

Your router should be configured with a rewrite rule which alters the default behavior of expedited forwarding as shown in the exhibit.

In this scenario, which configuration is correct?

- A.
- B.
- C.
- D.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 9

Which three statements are true about the show pim joinoutput shown in the exhibit? (Choose three.)

- A. The multicast stream does not have an RP.
- B. The shortest path to the source is through the RP.
- C. This is a source-specific multicast stream.
- D. The multicast receiver is still using the RP to receive the stream.
- E. The multicast stream has been configured with a backup path to allow for fast reroute.

Answer: A,B,E ([LEAVE A REPLY](#))

NEW QUESTION: 10

Exhibit:

Which two statements regarding the output shown in the exhibit are correct? (Choose two.)

- A. The type of connection is remote.
- B. The PEs have matching control word values.
- C. The label associated with this virtual circuit is out of range.

D. The type of connection is local.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 11

You are considering different MPLS VPN connectivity options of a new customer deployment Your customer requires shared LSPs Layer 2 connectivity and auto-provisioning Which type of VPN satisfies the requirements?

- A. circuit cross-connects
- B. BGP Layer 3 VPNs
- C. BGP Layer 2 VPNs
- D. LDP Layer 2 circuits

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 12

Exhibit.

R2 has IS-IS adjacencies with R3 and R4 You want to ensure that R2 has both a level 1 and level 2 adjacency to both R3 and R4 but R2 only has one adjacency with R4.

Referring to the exhibit, which configuration change will solve this issue?

- A. Change the IS-IS area on R2 to match R4.
- B. Remove the level 1 disable configuration from R4
- C. Remove the level 1 disable configuration from R2
- D. Change the IS-IS area on R4 to match R2

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 13

Which two statements about IS-IS are correct? (Choose two.)

- A. Level 1 intermediate systems exchange routing information with Level 1 intermediate systems in other IS-IS areas.
- B. An IS-IS router sets the attached bit in the PDUs it sends to a Level 1 area to indicate that it is a backbone router.
- C. A Level 1 router can only form adjacencies with other Level 1 routers.
- D. Level 2 routers can form adjacencies with either Level 1 or Level 2 routers.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 14

Exhibit.

You have the LDP signaled VPLS topology as shown in the exhibit CE-B at Site-2 is multihomed to both PE-2 and PE-3 In this scenario where would you configure loop prevention?

- A. PE-1
- B. PE-2
- C. CE-B

D. PE-3

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 15

Exhibit:

Which three statements are true about the show pim join output shown in the exhibit? (Choose three.)

- A. The multicast stream has been configured with a backup path to allow for fast reroute.
- B. This is a source-specific multicast stream. G The multicast receiver is still using the RP to receive the stream.
- C. The shortest path to the source is through the RP
- D. The multicast stream does not have an RP.

Answer: A,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 16

Exhibit:

Referring to the exhibit, which two statements are true? (Choose two.)

- A. The CE-1 and CE-2 routes will have the same route distinguisher, which will not stop the BGP routes from being shared.
- B. The CE-1 and CE-2 routes will have the same route distinguisher, which will stop the BGP routes from being shared.
- C. An AS loop will not exist between CE-1 and CE-2 and the BGP routes will be shared.
- D. An AS loop will exist between CE-1 and CE-2 and the BGP routes will not be shared.

Answer: A,D ([LEAVE A REPLY](#))

Valid JN0-663 Dumps shared by TrainingQuiz.com for Helping Passing JN0-663 Exam! TrainingQuiz.com now offer the **newest JN0-663 exam dumps**, the TrainingQuiz.com JN0-663 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com JN0-663 dumps with Test Engine here:
<https://www.trainingquiz.com/JN0-663-practice-quiz.html> (96 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 17

You want to allow the load balancing of traffic for an EBGp route from two different peers in the same AS.

Which three actions are needed to accomplish this task? (Choose three.)

- A. The multihop parameter should be configured under protocols BGP
- B. An equal cost AS path for the route is required.
- C. A policy to load-balance traffic should be applied to the forwarding table

- D. At least two interfaces should be connected to the same EBGP neighbor
- E. The multipath parameter should be configured under protocols BGP

Answer: C,D,E ([LEAVE A REPLY](#))

NEW QUESTION: 18

You recently deployed CoS-based forwarding in your network, which uses OSPF as its IGP. You notice that the forwarding of traffic has not changed and is not following the path indicated within your configuration.

In this scenario, which statement explains this behavior?

- A. The defined policy references IP addresses as the next-hops instead of interface names
- B. Load balancing has not been enabled under [edit forwarding-options].
- C. The defined policy has not been applied under [edit class-of-service forwarding-policy]
- D. The defined policy references interface names as the next-hops instead of IP addresses.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 19

Exhibit:

Referring to the exhibit, traffic sent from CE-A2 to PE3 does not loop back to CE-A2 through PE2. Which two EVPN functions accomplish this task? (Choose two.)

- A. multicast ingress replication
- B. split horizon
- C. aliasing
- D. designated forwarder election

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 20

Exhibit.

You are the administrator of AS 65512. You are learning the 192.168.1.0/24 prefix from both AS 100 and AS

200. You want traffic destined to the 192.168.1.0/24 prefix to exit your AS towards AS 200. How would you accomplish this task'?

- A. Configure an import routing policy on PE-2 to set a higher MED on the path learned from AS 100
- B. Configure an import routing policy on PE-2 to modify the origin attribute on the path learned from AS 100
- C. Configure an import routing policy on PE-2 to append the AS path attribute on the path learned from AS 100
- D. Configure an import routing policy on PE-2 to set a higher local preference value on the path learned from AS 200

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 21

A customer recently migrated to IS-IS and is concerned about resource starvation when the routing protocol daemon (RPD) starts.

To resolve this issue and protect R2 and R3, which feature should you implement?

- A.** Use the forwarding-options ip-options-protocol-queue parameter to increase resources.
- B.** Double the policy-options damping half-life timer to let the network settle.
- C.** Deploy firewall filters to limit the prefix count in the route table
- D.** Implement the overload bit and timer to signal service availability.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 22

Exhibit:

Referring to the exhibit, external routes are being received at R1. These routes must appear on R5.

Which action will produce this result?

- A.** Turn on wide metrics on R1 and R2 and write an export policy on R4 from level 2 to level 1 matching the external routes.
- B.** Turn on wide metrics on R4 and R5 and write an export policy on R2 from level 1 to level 2 matching the external routes.
- C.** Write an export policy on R2 from level 1 to level 2 matching the external routes.
- D.** Write an export policy on R4 from level 2 to level 1 matching the external routes.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 23

Exhibit:

A network administrator is migrating from IPv4 to IPv6 and one of the IS-IS adjacencies is not coming up between R1 and R2.

Which action will solve the problem?

- A.** Configure topologies ipv4-unicast from protocols isis on R2.
- B.** Configure an IPv4 address on interface ge-0/0/1 on R1.
- C.** Remove topologies ipv6-unicast from protocols isis on R1.
- D.** Remove topologies ipv6-unicast from protocols isis on R2.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 24

You want to allow the load balancing of traffic for an EBGP route from two different peers in the same AS.

Which three actions are needed to accomplish this task? (Choose three.)

- A.** A policy to load-balance traffic should be applied to the forwarding table

- B. The multihop parameter should be configured under protocols BGP
- C. The multipath parameter should be configured under protocols BGP
- D. At least two interfaces should be connected to the same EBGP neighbor
- E. An equal cost AS path for the route is required.

Answer: A,C,E ([LEAVE A REPLY](#))

NEW QUESTION: 25

You have a Layer 3 VPN established between PE-1 and PE-2 to allow communication between CE-1 and CE-2.

Referring to the exhibit, which statement is correct?

- A. You will need an OSPF import policy on PE-1 to receive the BGP routes, learned from PE-2, through the Layer 3 VPN.
- B. You will need a BGP export policy on PE-1 to redistribute the routes, learned from CE-1, through the Layer 3 VPN.
- C. You will need an OSPF export policy on PE-2 to redistribute the BGP routes, learned from PE-1, through the Layer 3 VPN.
- D. You will need a VRF import policy on PE-1 to advertise the BGP routes, learned from CE-1, through the Layer 3 VPN.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 26

Exhibit.

Referring to the exhibit, which statement is true?

- A. The BGP session between R1 and R2 will establish correctly and only the met unicast NLRI will pass routing information
- B. The BGP session between R1 and R2 will establish correctly and the met unicast and the met6 unicast NLRIs will pass routing information
- C. The BGP session between R1 and R2 will establish correctly and only the inet6 unicast NLRI will pass routing information
- D. The BGP session between R1 and R2 will fail to establish correctly due to an NLRI mismatch

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 27

Exhibit:

You are receiving the same 200.0.0.0/24 BGP route from four different ISPs.

Referring to the exhibit, which ISP's route would be selected as active?

- A. ISP-C
- B. ISP-A
- C. ISP-B
- D. ISP-D

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 28

Which two statements regarding ingress replication in EVPN are correct? (Choose two.)

- A. Ingress replication labels are learned from remote PEs through the EVPN Type-3 route.
- B. Ingress replication is only supported in vrf-type routing instances.
- C. Ingress replication relies on PIM to build the multicast replication tree.
- D. Ingress replication will replicate all BUM traffic to all remote PEs in the EVI.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 29

Exhibit:

R2 is receiving the same route from R1 and R3. You must ensure that you can load balance traffic for that route.

Referring to the exhibit, which two configuration changes will allow load balancing? (Choose two.)

- A. Apply the prepend policy as an import policy under group R3.
- B. Configure multipath under group R1.
- C. Apply the prepend policy as an import policy under group R1.
- D. Configure multipath under the global BGP configuration.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 30

Exhibit:

All adjacencies have been formed, no extra options have been configured, and no policies have been written.

Referring to the exhibit, which two statements are correct? (Choose two.)

- A. R1 can reach R5.
- B. R2 will create a default route and send it as a TLV to R1
- C. R1 cannot reach R5
- D. R1 will create its own default route that points to R2

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 31

Exhibit:

R1 assigns incoming voice traffic to the ef forwarding class. All other traffic is assigned to the best-effort forwarding class. You have configured a CoS re-write rule on R1 to include the correct CoS bit values in packets sent towards R2. You want R2 to classify traffic using the CoS markings created by R1.

Which two configuration steps are necessary to accomplish this task? (Choose two.)

- A. Assign the CoS re-write rule to the ge-0/0/1.0 interface on R2.
- B. Configure a CoS re-write rule on R2 and assign matching CoS values.
- C. Configure a behavior aggregate classifier on R2.

D. Assign the behavior aggregate classifier to the ge-0/0/1.0 interface on R2.

Answer: A,D ([LEAVE A REPLY](#))

Valid JN0-663 Dumps shared by TrainingQuiz.com for Helping Passing JN0-663 Exam! TrainingQuiz.com now offer the **newest JN0-663 exam dumps**, the TrainingQuiz.com JN0-663 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com JN0-663 dumps with Test Engine here:
<https://www.trainingquiz.com/JN0-663-practice-quiz.html> (96 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 32

Exhibit:

Referring to the ABR configuration shown in the exhibit, which three statements are correct?
(Choose three.)

- A. The ABR advertises a default route to the NSSA using a Type 7 LSA.
- B. The ABR advertises a single Type 3 summary LSA to the backbone area for all Type 1 and Type 2 LSAs in the 192.168.16.0/20 range.
- C. The ABR advertises a single Type 5 external LSA to the backbone area for all Type 7 LSAs in the NSSA.
- D. The ABR does not summarize any routes within the 192.168.16.0/20 range.
- E. The ABR advertises a Type 5 external LSA to the backbone area for each Type 7 LSA in the NSSA.

Answer: A,B,E ([LEAVE A REPLY](#))

NEW QUESTION: 33

Traffic is being sent from R2 to R3. The link between R2 and R3 fails.

Referring to the exhibit, which statement is correct?

- A. Manual intervention is required for traffic to be rerouted.
- B. Traffic will automatically reroute distributed between all available paths.
- C. Traffic will automatically reroute using the shortest path, which is R2 to R1 to R3.
- D. Traffic will automatically reroute using R2 to R4 to R1 to R3.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 34

Exhibit:

Traffic is being sent from R2 to R3. The link between R2 and R3 fails.

Referring to the exhibit, which statement is correct?

- A. Traffic will automatically reroute using the shortest path, which is R2 to R1 to R3.
- B. Manual intervention is required for traffic to be rerouted.

- C. Traffic will automatically reroute using R2 to R4 to R1 to R3.
- D. Traffic will automatically reroute distributed between all available paths.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 35

What information is stored in a VRF table for a BGP Layer 2 VPN? (Choose three.)

- A. Layer 2 encapsulation
- B. label-switched path
- C. remote interface of local CE device
- D. logical interface provisioned to local CE device local site ID

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 36

Exhibit:

Your network connects two segments of your customer's network as shown in the exhibit They need to exchange routes between Segment 1 and Segment 2 but both segments use the same AS number.

Which two steps will accomplish this task? (Choose two.)

- A. Configure the BGP group with the as-override parameter on routers R1 and R4.
- B. Configure the routing-options autonomous-system loops I parameter on routers R1 and R4.
- C. Configure the BGP group with the advertise-peer-as parameter on routers R2 and R3.
- D. Configure the routing-options autonomous-system loops I parameter on routers R2 and R3.

Answer: B,C ([LEAVE A REPLY](#))

NEW QUESTION: 37

Exhibit:

The exhibit shows a BGP peering session for two PE routers. The BGP session is up, but the hosts in the Layer

2 VPN that uses the BGP session are unable to communicate.

What is the problem in this situation?

- A. The BGP peer does not support the restarter functionality.
- B. The BGP peer does not support the add-path feature.
- C. There is a mismatch in the supported NLRI address families between the BGP peers.
- D. The local BGP router does not support Layer 2 VPN and Layer 3 VPN NLRI address families at the same time.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 38

Exhibit:

Referring to the exhibit, the local BGP router is receiving IPv4 routes from the BGP neighbor, but it is not receiving L3 VPN routes from the BGP neighbor.

Which two actions should you take to solve this problem? (Choose two.)

- A. Configure the family inet unicast statement on the BGP neighbor
- B. Configure the family inet unicast statement on the local BGP router.
- C. Configure the family inet-vpn unicast statement on the BGP neighbor.
- D. Configure the family inet-vpn unicast statement on the local BGP router.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 39

A customer wants to reduce LSP flooding in their IS-IS network.

Which parameter should you change to accomplish this task?

[edit protocols isis]

A. user@router# set lsp-interval 1000

[edit protocols isis interface <interface-name>]

B. user@router# set spf-options rapid-runs 5

[edit protocols isis interface <interface-name>]

C. user@router# set csnp-interval 65535

[edit protocols isis interface <interface-name>]

D. user@router# set mesh-group <mesh-group-number>

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 40

Exhibit:

You have a Layer 3 VPN established between PE-1 and PE-2 as well as between PE-1 and PE-3. You are using a route reflector (RR-1) to distribute VPN routes to your IBGP peers. You are asked to ensure that only relevant routes are sent from RR-1 to each of the PE routers.

Referring to the exhibit, which statement is correct?

- A. You should use firewall filtering on RR-1 and all the PE devices to control which routes are sent to each PE router.
- B. You should use route target filtering on RR-1 and all the PE devices to control which routes are sent to each PE router.
- C. You should use route target filtering only on RR-1 to control which routes are sent to each PE router.
- D. You should use VRF export policies on RR-1 to control which routes are sent to each PE router.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 41

You have an established Layer 3 VPN between two PE devices. You are asked to only send certain routes from PE-1 over the VPN to the remote site while maintaining all the routes on the PE-1 device. You created a policy that matches the specific routes and then tags these routes with the appropriate target community values.

In this scenario, which configuration changes must be made to satisfy the requirement?

- A.** Configure a RIB group and apply the policy as an import policy to routes distributed into the bgp.13vpn.0 routing table.
- B.** Configure the export parameter and apply the policy to the my-ext-groupBGP group configuration.
- C.** Configure the import parameter and apply the policy to the my-ext-groupBGP group configuration.
- D.** Configure the vrf-exportparameter and apply the policy under the edit routing-instances vpn-ahierarchy.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 42

Exhibit:

A network administrator is concerned about the number of LSAs that they are observing on the network.

What will reduce Type 7 LSAs advertised from R2 to the non-backbone routers shown in the exhibit?

- A.** Configure nssa under area 0.0.0.2 on R2.
- B.** Configure no-summaries under protocols ospf3 on R2.
- C.** Configure no-naaa-abr under protocols ospf3 on R2.
- D.** Configure no-summaries under area 0.0.0.2 on R2.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 43

Exhibit:

Referring to the exhibit, you need to implement VPLS between CE-A1 and CE-A2 You must ensure that no loops are created due to the multihoming of the connection from CE-A2 to PE2 and PE3.

Based on the type of VPLS, which two solutions will satisfy this requirement? (Choose two.)

- A.** In a BGP VPLS, configure a primary and backup neighbor.
- B.** In an LDP VPLS. configure multihoming and local preference on PE-2 and PE-3
- C.** In a BGP VPLS, configure multihoming and local preference on PE-2 and PE-3.
- D.** In an LDP VPLS, configure a primary and backup neighbor.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 44

Exhibit:

Referring to the exhibit, hosts in Site 1 and Site 2 are unable to communicate with each other through the Layer 3 VPN.

What is the problem?

- A.** The two sites are using the same instance type.

- B. The two sites are using the same route target.
- C. The two sites are in the same AS.
- D. The two sites are using the same route distinguishes.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 45

Exhibit:

Referring to the exhibit, which path would traffic passing through R1 take to get.

- A. R1 -> R3 -> R5 -> R6
- B. R1 -> R3 -> R4 -> R6
- C. R1 -> R2 -> R4 -> R6
- D. R1 -> R2 -> R3 -> R6

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 46

Exhibit:

CE-1, CE-2, and CE-3 are part of a single VPLS VPN. An Ethernet frame has just arrived at PE-3 from CE-3.

It has a source MAC address of CE-3 and a destination MAC address of CE-1. You want to know what PE-3 does with the Ethernet frame.

Referring to the exhibit, which statement is correct?

- A. It forwards the packet to PE-1 only.
- B. It drops the packet because the destination MAC address is not for PE-3.
- C. It drops the packet because the destination MAC address is not in PE-3's MAC table.
- D. It forwards the packet to PE-1 and PE-2.

Answer: ([SHOW ANSWER](#))

Valid JN0-663 Dumps shared by TrainingQuiz.com for Helping Passing JN0-663 Exam! TrainingQuiz.com now offer the **newest JN0-663 exam dumps**, the TrainingQuiz.com JN0-663 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com JN0-663 dumps with Test Engine here:
<https://www.trainingquiz.com/JN0-663-practice-quiz.html> (**96 Q&As Dumps, 40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 47

Exhibit:

You must configure an OSPF virtual link to facilitate communication between Area 0 and Area 20. Referring to the exhibit, which two addresses should you use as the neighbor IDs of the virtual link endpoints?

(Choose two.)

- A. The address that is associated with R4's xe-0/0/1 interface.
- B. The address that is associated with R2's router ID.
- C. The address that is associated with R2's xe-1/2/0 interface.
- D. The address that is associated with R4's router ID.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 48

What are two reasons an IBGP learned route would be hidden? (Choose two.)

- A. The route is suppressed by damping.
- B. The route has an empty AS path.
- C. The route has a next hop of the local routing device.
- D. The route is rejected by an export policy.

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 49

Exhibit:

All networks shown in the exhibit contain more than one BGP speaker You operate ISP A and must ensure that Customer Y sends their traffic to you over the directly connected link. Customer Y is not to be used for transit into your network.

What would you do to accomplish this task?

- A. Advertise routes to Customer X with the custom defined 0:0 community
- B. Advertise routes to Customer Y with the custom defined 65535:65535 community.
- C. Advertise routes to Customer Y with the well-known no-export community
- D. Advertise routes to Customer X with the well-known no-advertise community.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 50

Exhibit:

All networks shown in the exhibit contain more than one BGP speaker You operate ISP A and must ensure that Customer Y sends their traffic to you over the directly connected link. Customer Y is not to be used for transit into your network.

What would you do to accomplish this task?

- A. Advertise routes to Customer X with the custom defined 0:0 community
- B. Advertise routes to Customer X with the well-known no-advertise community.
- C. Advertise routes to Customer Y with the custom defined 65535:65535 community.
- D. Advertise routes to Customer Y with the well-known no-export community

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 51

Exhibit:

Referring to the exhibit, traffic sent from CE-A2 to PE3 does not loop back to CE-A2 through PE2. Which two EVPN functions accomplish this task? (Choose two.)

- A. designated forwarder election
- B. split horizon
- C. multicast ingress replication
- D. aliasing

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 52

All networks shown in the exhibit contain more than one BGP speaker. You operate ISP A and must ensure that Customer Y sends their traffic to you over the directly connected link. Customer Y is not to be used for transit into your network.

What would you do to accomplish this task?

- A. Advertise routes to Customer X with the custom defined 0:0 community.
- B. Advertise routes to Customer X with the well-known no-advertise community.
- C. Advertise routes to Customer Y with the custom defined 65535:65535 community.
- D. Advertise routes to Customer Y with the well-known no-export community.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 53

Exhibit:

You must configure an OSPF virtual link to facilitate communication between Area 0 and Area 20. Referring to the exhibit, which two addresses should you use as the neighbor IDs of the virtual link endpoints?

(Choose two.)

- A. The address that is associated with R2's xe-1/2/0 interface.
- B. The address that is associated with R2's router ID.
- C. The address that is associated with R4's xe-0/0/1 interface.
- D. The address that is associated with R4's router ID.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 54

Exhibit:

Referring to the exhibit, which two statements are correct? (Choose two.)

- A. R1 will never forward transit traffic through R2.
- B. R2 stops sending LSAs into the network.
- C. Transit traffic from R1 to R4 will traverse R3.
- D. The OSPF interface metrics on R2 are all set to 65535.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 55

You are deploying a new EVPN service for your customers. You must build the service based on the following requirements

-- both Layer 2 and Layer 3 functionality must be supported

-- your customers must be able to support multiple VLANs in the same EVPN instance (EVI).

In this scenario which two types of routing instances should be configured? (Choose two.)

- A. virtual switch
- B. VRF
- C. EVPN
- D. virtual router

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 56

You are establishing a Layer 3 VPN between two PE devices. Currently you have a single internal IPv4 BGP peering between the PE devices. You must ensure that the IPv4 and IPv6 routes from both CE devices are exchanged between these sites. Which two statements are correct in this scenario? (Choose two.)

- A. You must enable IPv6 tunneling on the LSPs between the PE devices
- B. You must enable the inet6-vpn NLRI on both PE devices.
- C. You must establish an IPv6 BGP peering between the two PEs
- D. You must enable the inet-vpn NLR on both PE devices.

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 57

Which statement is correct about BGP FlowSpec between a service provider's PE router and a customer?

- A. The NLRI received from a customer is stored in the inetflow.0 table
- B. The flow routes received from a customer are limited to /32 masks for IPv4.
- C. The NLRI received from a customer is stored in the flowspec. inet .0 table.
- D. The RFC deterministic traffic filtering algorithm is used by default in Junos.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 58

Exhibit:

The exhibit shows a BGP peering session for two PE routers. The BGP session is up, but the hosts in the Layer

2 VPN that uses the BGP session are unable to communicate.

What is the problem in this situation?

- A. There is a mismatch in the supported NLRI address families between the BGP peers.
- B. The local BGP router does not support Layer 2 VPN and Layer 3 VPN NLRI address families at the same time.
- C. The BGP peer does not support the add-path feature.

D. The BGP peer does not support the restarter functionality.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 59

Referring to the exhibit, which statement is true?

- A. The BGP session between R1 and R2 will establish correctly and only the inet6 unicast NLRI will pass routing information.
- B. The BGP session between R1 and R2 will fail to establish correctly due to an NLRI mismatch.
- C. The BGP session between R1 and R2 will establish correctly and only the inet unicast NLRI will pass routing information.
- D. The BGP session between R1 and R2 will establish correctly and the inet unicast and the inet6 unicast NLRIs will pass routing information.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 60

Exhibit:

Referring to the exhibit, external routes are being received at R1. These routes must appear on R5.

Which action will produce this result?

- A. Write an export policy on R2 from level 1 to level 2 matching the external routes.
- B. Write an export policy on R4 from level 2 to level 1 matching the external routes.
- C. Turn on wide metrics on R1 and R2 and write an export policy on R4 from level 2 to level 1 matching the external routes.
- D. Turn on wide metrics on R4 and R5 and write an export policy on R2 from level 1 to level 2 matching the external routes.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 61

Exhibit:

You have a Layer 3 VPN established between PE-1 and PE-2 as well as between PE-1 and PE-3. You are using a route reflector (RR-1) to distribute VPN routes to your IBGP peers. You are asked to ensure that only relevant routes are sent from RR-1 to each of the PE routers.

Referring to the exhibit, which statement is correct?

- A. You should use firewall filtering on RR-1 and all the PE devices to control which routes are sent to each PE router.
- B. You should use VRF export policies on RR-1 to control which routes are sent to each PE router.
- C. You should use route target filtering on RR-1 and all the PE devices to control which routes are sent to each PE router.
- D. You should use route target filtering only on RR-1 to control which routes are sent to each PE router.

Answer: D ([LEAVE A REPLY](#))

Valid JN0-663 Dumps shared by TrainingQuiz.com for Helping Passing JN0-663 Exam! TrainingQuiz.com now offer the **newest JN0-663 exam dumps**, the TrainingQuiz.com JN0-663 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com JN0-663 dumps with Test Engine here:
<https://www.trainingquiz.com/JN0-663-practice-quiz.html> (96 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

NEW QUESTION: 62

Exhibit:

You notice an inconsistency between the routing table and the OSPF database, as shown in the exhibit.

What are two reasons for this behavior? (Choose two.)

- A. The LSA is a Type 5 LSA.
- B. An OSPF import policy is being applied to the route.
- C. The LSA is a Type 4 LSA.
- D. An OSPF export policy is being applied to the route.

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 63

Exhibit:

The route shown in the exhibit is an example of which type of next-generation MVPN route?

- A. Type 1 Intra-AS inclusive MVPN membership discovery
- B. Type 3 Selective MVPN autodiscovery route
- C. Type 4 Selective MVPN autodiscovery route for leaf
- D. Type 2 Inter-AS inclusive MVPN membership discovery

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 64

Exhibit:

Referring to the exhibit, what will the IS-IS cost be for R1 to reach R3?

- A. 20
- B. 301
- C. 73
- D. 310

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 65

Exhibit:

You are receiving the same 200.0.0.0/24 BGP route from four different ISPs.

Referring to the exhibit, which ISP's route would be selected as active?

- A. ISP-A
- B. ISP-C
- C. ISP-D
- D. ISP-B

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 66

Exhibit:

Referring to the exhibit, which two statements are correct? (Choose two.)

- A. The OSPF interface metrics on R2 are all set to 65535.
- B. R2 stops sending LSAs into the network.
- C. Transit traffic from R1 to R4 will traverse R3.
- D. R1 will never forward transit traffic through R2.

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 67

You are responsible for configuring CoS for your network. Your network includes a video application with strict latency requirements, so that any packets delayed by more than 75 ms are effectively useless. You want to ensure that you do not waste buffer space.

When configuring the scheduler for this application, which feature would you use?

- A. exact
- B. remainder
- C. rate limit
- D. temporal

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 68

Referring to the exhibit, there is a Layer 3 VPN setup that connects sites CE-A-1, CE-A-2, and CE-A-3 together. Host-1 can communicate with Host-3, but Host-1 cannot communicate with Host-2.

What must you do to solve the problem?

- A. Change the route distinguisher in both routing instances to the same value.
- B. Use the auto-export command in both routing instances.
- C. Use the next-table configuration statement for static routes in the corresponding routing instances.
- D. Use BGP instead of static routing between the CE and PE devices.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 69

Exhibit:

You have an established Layer 3 VPN between two PE devices. You are asked to only send certain routes from PE-1 over the VPN to the remote site while maintaining all the routes on the PE-1 device. You created a policy that matches the specific routes and then tags these routes with the appropriate target community values.

In this scenario, which configuration changes must be made to satisfy the requirement?

- A. Configure the import parameter and apply the policy to the my-ext-group BGP group configuration.
- B. Configure the export parameter and apply the policy to the my-ext-group BGP group configuration.
- C. Configure the vrf-export parameter and apply the policy under the edit routing-instances vpn-a hierarchy.
- D. Configure a RIB group and apply the policy as an import policy to routes distributed into the bgp I3vpn.0 routing table

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 70

Exhibit:

All adjacencies have been formed, no extra options have been configured, and no policies have been written.

Referring to the exhibit, which two statements are correct? (Choose two.)

- A. R1 will create its own default route that points to R2
- B. R1 can reach R5.
- C. R1 cannot reach R5
- D. R2 will create a default route and send it as a TLV to R1

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 71

Exhibit:

Referring to the exhibit, which three statements are correct? (Choose three.)

- A. The ESI is 00:22:22:22:22:22:22:22:22:22.
- B. This route contains the MAC address of an end host.
- C. The router with the IP address 10.101.100.3 is the originator of this route.
- D. This ESI Auto-Discovery route is used for designated forwarder election.
- E. This route is an EVPN Type-1 route.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 72

Exhibit:

Referring to the exhibit, which three statements are correct? (Choose three.)

- A. This route is an EVPN Type-1 route.
- B. The router with the IP address 10.101.100.3 is the originator of this route.
- C. This route contains the MAC address of an end host.
- D. This ESI Auto-Discovery route is used for designated forwarder election.
- E. The ESI is 00:22:22:22:22:22:22:22:22.

Answer: A,B,E ([LEAVE A REPLY](#))

NEW QUESTION: 73

Exhibit:

Referring to the exhibit, which statement is true?

- A. The route is learned from only one neighbor.
- B. This is a multipath route.
- C. This is a multihop route.
- D. The route is learned from three different neighbors.

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 74

Exhibit:

Your network connects two segments of your customer's network as shown in the exhibit They need to exchange routes between Segment 1 and Segment 2 but both segments use the same AS number.

Which two steps will accomplish this task? (Choose two.)

- A. Configure the BGP group with the as-override parameter on routers R1 and R4.
- B. Configure the routing-options autonomous-system loops I parameter on routers R2 and R3.
- C. Configure the BGP group with the advertise-peer-as parameter on routers R2 and R3.
- D. Configure the routing-options autonomous-system loops I parameter on routers R1 and R4.

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 75

The link between CE1 and PE1 has a history of flapping To avoid the impact that flapping causes to the network you decide to use route damping Which statement is correct in this scenario?

- A. Dampened routes become active when their figure of merit drops below the reuse value.
- B. Dampening is enabled on interfaces
- C. Routes become dampened when the configured max-suppress value is reached
- D. Dampened routes decay at a sliding rate known as half-life

Answer: D ([LEAVE A REPLY](#))

JN0-663 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com JN0-663 dumps with Test Engine here:

<https://www.trainingquiz.com/JN0-663-practice-quiz.html> (96 Q&As Dumps, **40%OFF** Special

Discount: **Exam-Tests**)