

## NetworkAppliance.NS0-184.v2022-12-17.q39

Exam Code:	NS0-184
Exam Name:	NetApp Certified Storage Installation Engineer, ONTAP
Certification Provider:	Network Appliance
Free Question Number:	39
Version:	v2022-12-17
# of views:	909
# of Questions views:	390
<a href="https://www.dumpsdb.com/dumps/NetworkAppliance/NS0-184/NetworkAppliance.NS0-184.v2022-12-17.q39">https://www.dumpsdb.com/dumps/NetworkAppliance/NS0-184/NetworkAppliance.NS0-184.v2022-12-17.q39</a>	

### NEW QUESTION: 1

Your customer wants to know more about the network configuration within the cluster.

In this scenario, which statement is correct about a LIF?

- A. A LIF is created within a broadcast domain and contains a pool of IP address.
- B. A LIF is an IP address or a WWPN that is associated with a port.
- C. A LIF separates network domains to access cluster data.
- D. A LIF is a port that provides physical connections.

Answer: [\(SHOW ANSWER\)](#)

### NEW QUESTION: 2

What should you do to change the data protocol of a LIF?

- A. Put the LIF in another broadcast domain.
- B. Delete and re-recreate the LIF.
- C. Add the new data protocol to the LIF.
- D. Shut down the assigned port.

Answer: [B \(LEAVE A REPLY\)](#)

### NEW QUESTION: 3

Your customer wants a newly installed AFF C190 cluster to send SNMP notifications to a trap host called OVERWATCH01.

In this scenario, which two statements are correct? (Choose two.)

- A. Configure a trap host on the cluster.
- B. Configure a firewall policy and allow SNMP.
- C. Configure DNS on the cluster.

D. Configure an SNMP community string on the cluster.

**Answer:** ([SHOW ANSWER](#))

**NEW QUESTION: 4**

You are preparing to physically install a new AFF A400 cluster into a customer's racks. All equipment has been delivered to the customer's site.

Which three tools do you need to complete this installation? (Choose three.)

- A. additional network cables
- B. Phillips #2 screwdriver
- C. cable management tray
- D. laptop computer
- E. slide rail kit

**Answer:** A,B,D ([LEAVE A REPLY](#))

**NEW QUESTION: 5**

A customer is asked to install a new AFF ASA A700 system. During the installation, the customer asks if ONTAP 9.8 is supported with their host's OS version running Windows 2016.

In this scenario, which NetApp tool would verify supportability?

- A. Active IQ Unified Manager
- B. Active IQ OneCollect
- C. ONTAP System Manager
- D. Interoperability Matrix Tool

**Answer:** C ([LEAVE A REPLY](#))

**NEW QUESTION: 6**

A customer wants to enable SnapMirror Synchronous across their environment. The customer must ensure that SnapMirror Synchronous will work across the environment.

In this scenario, which two statements are true? (Choose two.)

- A. A SnapMirror license is not required on both the source cluster and the destination cluster.
- B. A SnapMirror Synchronous license is required on the source cluster.
- C. A SnapMirror Synchronous license is required on both the source and destination clusters.
- D. A SnapMirror license is required on both the source cluster and the destination cluster.

**Answer:** A,C ([LEAVE A REPLY](#))

**NEW QUESTION: 7**

You are deploying a new AFF All SAN Array A250 into a customer's existing data fabric.

In this scenario, which two tools would give insight into their existing Cisco MDS fabric configuration? (Choose two.)

- A. Brocade SAN Health
- B. Cisco Data Center Network Manager (DCNM)
- C. Active IQ

D. Active IQ Config Advisor

**Answer: B,C (LEAVE A REPLY)**

Reference:

<https://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-x-series-modular-system/flex-pod-datacenter-ucs-intersight.html>

**NEW QUESTION: 8**

Which two SVMs are automatically created during the cluster setup? (Choose two.)

A. system SVM

B. admin SVM

C. data SVM

D. node SVM

**Answer: A,B (LEAVE A REPLY)**

**NEW QUESTION: 9**

Click the Exhibit button.



Which set of components on a FAS9000 are highlighted in the exhibit?

A. Powersupply, Controller, USB-Port, NVRAM-Module

B. NVRAM-Module, Controller, Serial-Port, FlashCache-Module

C. FCVI-Module, Controller, Serial-Port, FlashCache-Module

D. SAS-Module, Controller, USB-Port, FlashCache-Module

**Answer: C ([LEAVE A REPLY](#))**

**NEW QUESTION: 10**

You have installed a new 2-node FAS9000 cluster with two external shelves. You want to make sure that each node has two paths to each disk in the shelves.

How do you verify your configuration?

- A. Use the disk show -fields initiator command.
- B. Use the storage disk option show command.
- C. Use the storage show disk -p command.
- D. Use the sysconfig command.

**Answer: A ([LEAVE A REPLY](#))**

**NEW QUESTION: 11**

You are expanding an existing cluster that uses BES-53248 cluster interconnect switches. You connected the new controllers to ports 0/17 through 0/20. However, you are unable to join the new nodes to the cluster.

Which action must be taken to solve the problem?

- A. Install the license file.
- B. Install the reference configuration file.
- C. Install the CSHM configuration file.
- D. Reboot the controllers.

**Answer: B ([LEAVE A REPLY](#))**

**NEW QUESTION: 12**

You are planning to install a new ONTAP 9.7 All SAN Array (ASA) into your existing data center.

In this scenario, which cluster configuration is allowed with ASA controllers?

- A. ASA controllers can only be installed as a standalone HA pair.
- B. Add the ASA controllers to an existing 4-node cluster with NAS licenses.
- C. Add the ASA controllers to an existing 10-node cluster.
- D. ASA controllers can only be added to clusters that have existing SAN licenses.

**Answer: ([SHOW ANSWER](#))**

**NEW QUESTION: 13**

You have just finished installing and configuring an ONTAP cluster for a customer.

In this scenario, which product collects information and produces site documentation?

- A. Active IQ OneCollect
- B. Inventory Collect Tool
- C. SnapGathers
- D. NetAppDocs

**Answer: D ([LEAVE A REPLY](#))**

**NEW QUESTION: 14**

After moving a new AFF A400 cluster into production, the administrator notices error events in ONTAP System Manager regarding SAS HA issues.

In this scenario, which NetApp tool would have identified these errors after the installation process?

- A. ONTAP System Manager
- B. Active IQ Config Advisor
- C. Cloud Manager
- D. Active IQ Unified Manager

**Answer:** ([SHOW ANSWER](#))

#### NEW QUESTION: 15

You have an AFF All SAN Array (ASA) cluster that is running ONTAP 9.7. The cluster is configured for Active Directory domain controller access using a domain tunnel.

In this scenario, which two licenses are enabled on the cluster? (Choose two.)

- A. CIFS
- B. NVMe
- C. iSCSI
- D. FCP

**Answer:** A,D ([LEAVE A REPLY](#))

#### NEW QUESTION: 16

You have completed a base installation and system registration of an AFF A250 system, but you notice that you have one failed drive. Neither "un-failing" nor reseating the drive helped to repair it. You must ensure proper replacement of the failed drive.

In this scenario, which two actions should you take? (Choose two.)

- A. Run Active IQ Config Advisor to collect all the logs on the system.
- B. Ask the customer to open a technical case with NetApp Support.
- C. Power off the system until the drive has been replaced.
- D. Ask the customer for a drive with the same capacity and replace it.

**Answer:** A,D ([LEAVE A REPLY](#))

**Valid NS0-184 Dumps** shared by TrainingQuiz.com for Helping Passing NS0-184 Exam!

TrainingQuiz.com now offer the **newest NS0-184 exam dumps**, the TrainingQuiz.com NS0-184 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com NS0-184 dumps with Test Engine here: <https://www.trainingquiz.com/NS0-184-practice-quiz.html> (60

Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

#### NEW QUESTION: 17

An ONTAP cluster is installed at a secure site. The array has no access to the Internet but is managed 24/7 by onsite engineers. The customer requires that when hardware failures occur, the failures are reported to the NetApp Support team as quickly as possible.

In this scenario, which two tasks should be performed during the project hand-off procedure to satisfy the customer's requirement? (Choose two.)

- A. Ensure that Active IQ Config Advisor is installed.
- B. Educate the onsite engineer about how to manually log support calls.
- C. Ensure that the onsite engineers receive EMS alerts when hardware issues occur.
- D. Educate the onsite engineers about invoking the AutoSupport tool from ONTAP System Manager.

**Answer:** ([SHOW ANSWER](#))

### NEW QUESTION: 18

Click the Exhibit button.

```
welcome to node setup.
```

```
You can enter the following commands at any time:
```

```
"help" or "?" - if you want to have a question clarified,  
"back" - if you want to change previously answered questions, and  
"exit" or "quit" - if you want to quit the setup wizard.  
Any changes you made before quitting will be saved.
```

```
To accept a default or omit a question, do not enter a value.
```

```
Enter the node management interface port [e0c1]:
```

You want to add a FAS2750 HA pair to an existing 6-node cluster.

Referring to the exhibit, which action would you perform to begin adding the node?

- A. Use the back command to begin the Cluster Setup wizard.
- B. Reboot the node and enter maintenance mode and run the Cluster Setup wizard.
- C. Use the node setup wizard and select 0a as the management interface.
- D. Use the exit or quit commands then run the cluster setup command.

**Answer:** ([SHOW ANSWER](#))

### NEW QUESTION: 19

Which command would be used to measure the throughput and latency of traffic between nodes?

- A. qos statistics workload performance show
- B. statistics node show
- C. cluster ping-cluster
- D. network test-path

**Answer:** D ([LEAVE A REPLY](#))

### NEW QUESTION: 20

You have a new 2-node FAS8700 ONTAP 9.8 cluster. One of the nodes has 24x16 TB NL-SAS disks assigned and available for a new aggregate. You created the aggregate with one RAID group and two spare disks.

In this scenario, how many data drives are in the aggregate?

- A. 20
- B. 18
- C. 19
- D. 17

**Answer: A** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 21**

You use the system health subsystem show command to troubleshoot your newly installed ONTAP cluster. In this scenario, which two health outputs would this command show you? (Choose two.)

- A. node CPU utilization
- B. cluster switch cabling
- C. data switch cabling
- D. shelf connectivity

**Answer:** ([SHOW ANSWER](#))

#### **NEW QUESTION: 22**

A customer is creating a new SVM to host iSCSI LUNs for a Hyper-V cluster. You need to successfully map the new LUNs and make them visible to the Hyper-V cluster.

In this scenario, which host information is required to accomplish this task?

- A. WWNNs
- B. WWPNS
- C. host names
- D. IQNs

**Answer: C** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 23**

You are installing a new ONTAP 9.7 cluster by following the installation and setup poster. You are ready to complete the initial cluster setup. You have connected your laptop to the management switch. However, when browsing the network, you are unable to discover the ONTAP controllers.

Which statement explains this behavior?

- A. You do not have a static IP address.
- B. You do not have network discovery enabled.
- C. You do not have a default gateway set.
- D. You do not have IPv6 configuration set.

**Answer: C** ([LEAVE A REPLY](#))

#### **NEW QUESTION: 24**

After the Installation of a new NetApp FAS system, you use theNetAppDocs tool for site design documentation.

In this scenario, in which three document formats would you create an inventory report? (Choose three.)

- A. .xlsx
- B. .ps
- C. .docx
- D. .pdf
- E. .html

**Answer: C,D,E ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 25**

After a system panic, the NetApp Support team advises you to run the sdiag command. Which two actions must be performed before you use this command? (Choose two.)

- A. At the storage system prompt, type boot\_maintenance.
- B. At the LOADER prompt, type boot\_maintenance.
- C. At the LOADER prompt, type boot\_diags.
- D. At the storage system prompt, type halt.

**Answer: C,D ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 26**

Click the Exhibit button.

```
::> event notification destination create -name syslog -syslog 10.10.100.40
::> event notification create -filter-name important-events -destinations syslog
::> cluster log-forwarding create -destination 10.10.100.40 -port 514 -facility user
```

Referring to the exhibit, what information is forwarded to syslog after you enter the scripted install commands? (Choose two.)

- A. AutoSupport messages
- B. SNMP traps
- C. EMS messages
- D. command history

**Answer: A,D ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 27**

You installed a new pair of Cisco 92300YC cluster switches at a customer's site. Before you install any files on the switch, you want to view the current configuration.

In this scenario, which command would you use to accomplish this task?

- A. fabricshow
- B. config show
- C. switchcfgshow
- D. show running-config

**Answer: C ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 28**

You need to install a cluster with a FAS2720 HA pair and a FAS8300 HA pair.

Which NetApp tool will verify which cluster interconnect switches support this configuration?

- A. Hardware Universe (HWU)
- B. Active IQ Config Advisor
- C. mysupport.netapp.com site
- D. Interoperability Matrix Tool (IMT)

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 29**

You are installing a new FAS2750 cluster with 24 HDDs for a customer to run a NAS workload. The customer requests that the HA pair have only a single aggregate that is located on Node 1. Maximum capacity is required.

Which action must be performed to ensure that the customer's requests are satisfied?

- A. Assign all data LIFs to Node 1.
- B. Assign all the partitioned disks from Node 2 to Node 1, and create a single aggregate.
- C. Assign all the data partitions from Node 2 to Node 1, and create a single aggregate.
- D. Perform a takeover of Node 2 to ensure that it does not run.

**Answer: A ([LEAVE A REPLY](#))**

#### **NEW QUESTION: 30**

You are preparing for the installation of a new 2-node cluster with ONTAP 9.7 using NL-SAS drives. Your customer wants to use the cluster exclusively with FlexGroups.

In this scenario, which two statements are correct? (Choose two.)

- A. A NAS protocol is licensed on both nodes.
- B. A SAN protocol is licensed on both nodes.
- C. All NL-SAS drives are divided evenly across both nodes.
- D. All NL-SAS drives are assigned only to one of the nodes.

**Answer: ([SHOW ANSWER](#))**

#### **NEW QUESTION: 31**

You have an AFF A400 cluster that is running ONTAP 9.7 software. You are asked to set up FlexCache for NFS volumes.

In this scenario, which statement is correct when implementing FlexCache?

- A. A subscription license is required.
- B. A site license is required.
- C. No license is required.
- D. A capacity license is required.

**Answer: ([SHOW ANSWER](#))**

**Valid NS0-184 Dumps** shared by TrainingQuiz.com for Helping Passing NS0-184 Exam!  
TrainingQuiz.com now offer the **newest NS0-184 exam dumps**, the TrainingQuiz.com NS0-184 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com NS0-184 dumps with Test Engine here: <https://www.trainingquiz.com/NS0-184-practice-quiz.html> (60 Q&As Dumps, **40%OFF Special Discount: Exam-Tests**)

#### **NEW QUESTION: 32**

You are adding new controllers to an existing cluster. As part of the upgrade process, you have updated the BES-53248 cluster switches.

In this scenario.

Which two commands would you use to verify a healthy cluster after the upgrade? (Choose two.)

- A. network interface show -vserver Cluster
- B. network port show -ipspace Cluster
- C. network device-discovery show -protocol cdp
- D. network interface show -vserver Cluster -fields auto-revert

**Answer: A,B (LEAVE A REPLY)**

#### **NEW QUESTION: 33**

You must replace a FAS2750 switchless cluster with an AFF A220 switchless cluster for a customer. The customer requires that you transfer the data from the FAS2750 cluster to the AFF A220.

In this scenario, which two methods would you use to migrate the customer's data? (Choose two.)

- A. Establish an SVM-DR relationship between the two clusters and activate the destination SVM.
- B. Provide cluster switches and build a 4-node cluster, then use the vol move command.
- C. Remove all of the HDD drives from the FAS cluster and install them into the AFF cluster.
- D. Install SAS cables between the two clusters and use the vol move command.

**Answer: B,D (LEAVE A REPLY)**

#### **NEW QUESTION: 34**

What is the default shelf ID for disk shelves with IOM12 modules?

- A. 01
- B. 12
- C. 00
- D. 10

**Answer: C (LEAVE A REPLY)**

#### **NEW QUESTION: 35**

You are installing a new six-node ONTAP 9.8 cluster. You have completed the initial configuration of the cluster interconnect switches and the ONTAP cluster.

In this scenario, which feature should you enable?

- A. data center bridging protocol

- B. cluster switch health monitor
- C. IPv6 on all cluster ports
- D. cluster switch logging

**Answer: B** ([LEAVE A REPLY](#))

#### NEW QUESTION: 36

Click the Exhibit button.



You are installing a 2-node AFF A400 switchless cluster. You have cabled the management network to the e0M port. NetApp also recommends cabling to a redundant management network switch.

Referring to the exhibit, to which port should the redundant management network be cabled?

- A. 4
- B. 1
- C. 3
- D. 2

**Answer: (SHOW ANSWER)**

#### NEW QUESTION: 37

A storage administrator is trying to upgrade a pair of FAS2520s with internal SATA storage to a new 2-node FAS8300 cluster. The storage administrator wants to preserve the existing data.

In this scenario, which two capabilities are available to the storage administrator? (Choose two.)

- A. the ability to move the volumes from the old nodes to the new nodes
- B. the ability to convert the FAS2520s to disk shelves and attach them to the new nodes
- C. the ability to pull out the tray of internal disks of the FAS2520s and reseal the tray in the internal storage of the FAS8300s
- D. the ability to create a 4-node MetroCluster across the four nodes

**Answer: (SHOW ANSWER)**

#### NEW QUESTION: 38

You are installing an AFF A700 system with two disk shelves using ADPv2. After setting up the cluster, you realize that one drive shelf was powered off and that the drives have not been assigned to any of the nodes.

In this scenario, which two resources will help you find a solution? (Choose two.)

- A. NetApp Knowledge Base
- B. Active IQ Config Advisor
- C. NetApp Documentation Center
- D. Active IQ Digital Advisor

**Answer: A,B** ([LEAVE A REPLY](#))

**NEW QUESTION: 39**

You have added two new AFF A250 nodes to an existing 4-node cluster with NetApp CN1610 cluster network switches. Although the nodes can join the cluster, the storage failover show command output shows that the NVRAM log is not synchronized, and it cannot reach the partner over an HA interconnect.

In this scenario, which two statements are true? (Choose two.)

- A. The AFF A250 requires switches with 40GbE port support.
- B. The AFF A250 requires switches with 25GbE port support.
- C. The AFF A250 uses different ports for the cluster and the HA interconnect.
- D. The AFF A250 uses the same port for the cluster and the HA interconnect.

**Answer: B,C ([LEAVE A REPLY](#))**

**Valid NS0-184 Dumps** shared by TrainingQuiz.com for Helping Passing NS0-184 Exam!

TrainingQuiz.com now offer the **newest NS0-184 exam dumps**, the TrainingQuiz.com NS0-184 exam **questions have been updated** and **answers have been corrected** get the **newest** TrainingQuiz.com NS0-184 dumps with Test Engine here: <https://www.trainingquiz.com/NS0-184-practice-quiz.html> (**60** Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)